



www.accesshoseintl.com

ACCESS HOSE INTERNATIONAL, INC.

WAREHOUSE ORDERS: 12250 KINDRED LANE, HOUSTON, TEXAS 77049
SALES # 281-458-5133 / FAX # 281-458-5372 Email: scot@accesshoseintl.com
SERVING YOU IN 2 LOCATIONS: HOUSTON, TX & ATLANTA, GA

DIN 2022 - 1SN / SAE 100 R1AT REELS THRU 1" I.D.

EXCEEDS SAE 100 R1AT PRESSURES WITH THE SAME DIMENSIONS & FLEXIBILITY

TUBE : Black synthetic rubber seamless and resistant to oils

COVER : Black oil & abrasion resistant synthetic rubber

REINFORCEMENT : High Tensile Steel Braid

TEMP. RANGE : minus 40 deg to 250 deg F

1SN 1" I.D. 1276 PSI W.P.

| <u>Part #</u> | <u>I.D.</u> | <u>O.D.</u> | <u>BRAIDS</u> | <u>W.P. PSI</u> | <u>B.P. PSI</u> | <u>Bend Radius</u> | <u>Weight/lb.</u> |
|---------------|-------------|-------------|---------------|-----------------|-----------------|--------------------|-------------------|
| R1T03 | 3/16" | .464" | 1 | 3625 | 14500 | 3.5" | 0.13 |
| R1T04 | 1/4" | .528" | 1 | 3265 | 13060 | 3.9" | 0.15 |
| R1T05 | 5/16" | .591" | 1 | 3120 | 12480 | 4.5" | 0.18 |
| R1T06 | 3/8" | .685" | 1 | 2610 | 10440 | 5.1" | 0.23 |
| RIT08 | 1/2" | .807" | 1 | 2310 | 9280 | 7.1" | 0.29 |
| RIT10 | 5/8" | .933" | 1 | 1885 | 7560 | 7.9" | 0.36 |
| RIT12 | 3/4" | 1.091" | 1 | 1525 | 6100 | 9.5" | 0.41 |
| R1T16 | 1" | 1.402" | 1 | 1276 | 5100 | 11.8" | 0.51 |
| R1T20 | 1 1/4" | 1.811" | 1 | 914 | 3660 | 16.5" | 0.79 |
| R1T24 | 1 1/2" | 2.063" | 1 | 725 | 2900 | 19.7" | 1.06 |
| R1T32 | 2" | 2.626" | 1 | 580 | 2320 | 24.8" | 1.42 |

Lengths: Reels through size 16 (1') 20, 24, 32 sizes 50', 100', 150' (1pc)

40+48 sizes 50', 100' maximum Fabrication Available. Call Sales.



INTERNATIONAL

Ph. 281-458-5133

Fax 281-458-5372

www.accesshoseintl.com